

**Continuous Group Limited - Building Product Information – 100x55mm Ezi-Flo downpipe system**

Product and manufacturer details	
Product Name:	100x55mm Ezi-Flo downpipe system
Product Identifier:	10055EFSPA-SYS
Manufacturer's Name & Address	Refer to table 3 for Continuous Group branded manufacturing locations and/or supply.
Manufacturer's Email Address	<a href="mailto:cg@continuous.co.nz">cg@continuous.co.nz</a>
Manufacturer's Web Address	<a href="http://www.continuous.co.nz">www.continuous.co.nz</a>
Place of Manufacture	Aotearoa New Zealand
Warnings & Bans	No

**Product description**

100x55mm Ezi-Flo downpipe system is an external downpipe system designed to collect and drain water from a spouting or rainwater head. To complete the installation of this system the following components are required.

**Table 1**

System Components	Component - Material
100x55mm Ezi-Flo Series downpipe	Manufactured from 1.9mm BMT extruded Aluminium, Grade 6060 T5 - Powder coated
100x55mm brackets	Minimum LM2 grade Diecast aluminium – Powder coated
100x55mm Bends, Tees and joiners	Minimum LM2 grade Diecast aluminium – Powder coated
Fastenings/Fixings	Minimum Class 4 coated steel screws with a minimum 2.8mm depth head height and minimum 8 gauge screw thickness. Minimum 4/3 aluminium rivet fasteners.
Sealant	<b>Recommended:</b> Selleys (Admil) Mastersil SMP25, Silane based adhesive <b>Acceptable:</b> Industrial grade 100% silicone fit for external application

**Specifications & Installation Requirements**

100x55mm Ezi-Flow downpipe system is an external downpipe system designed with the following system specifications when installed as per instructions.

**Table 2**

System details	Specification / Installation
Pre-Installation design	Designers must review system capacities required before specifying this system by utilising online calculators available on the NZMRM website.
Outlet Cross Section Capacity	4925mm <sup>2</sup>
Maximum Bracket Spacing	2400mm (it is recommended that brackets are placed within 400mm of bends, tees and drain connections)
Angle of installation	Vertically and/or no less than 5 degrees of fall.

**Scope of use**

100x55mm Ezi-Flow downpipe system is an external downpipe system designed to collect and channel water that runs out of the gutter or rainwater head. It is intended that the system will be positioned outside of the building envelope.

**Continuous Group Limited - Building Product Information – 100x55mm Ezi-Flo downpipe system**

**Limitations of the use of this building product:**

1. All Continuous Group Downpipe Systems should only be installed by a trade professional.
2. The system cannot be installed onto spouting, rain heads or cladding with incompatible materials. The system cannot run-off onto incompatible materials. Material Compatibility, Contact and Run off to be adhered to in accordance with E2/AS1 Table 20, 21 & 22
3. The system cannot be used as an “Internal downpipe”.
4. The system can be used for gravity feed and “Charged” system (Occurs when rainwater collection tanks are above ground level).
5. The System uses various components as specified in *table 1*. These components make up the entire system and cannot be substituted under any circumstances.
6. Site locations must be evaluated in areas with high wind &/or salt &/or thermal/industrial atmospheric conditions. These types of locations may require specific engineering design (SED). Designers must consult metal supplier’s information for specific durability requirements (Reference E2/AS1 table 20)

**Maintenance Requirements**

*(Link to Care and Maintenance Document below under “Supporting Documentation”)*

1. Inspection of the system is required every 3 months to check for buildup of residue and organic matter inside and outside of the system.
2. Wash the painted surface of the System at a minimum of every 6 months and immediately after inspection if required.
3. Remove any debris from the inside of the downpipe at least every 6 months and immediately after inspection if required.

**Relevant building code clauses.**

Compliance/Regulation	Detail
E1/AS1 Surface water	Sections: 4.1.1, 4.1.2 & 4.2.1
E2/AS1 External Moisture	Table 20,21 & 22
AS/NZS 2179.1.2014	Section: 2.2.2, 3.5 & Table 3.3
B2/AS1	Table 1: Durability Requirements of Nominated Building Element
Code of practice V23.09	Sections as noted in reference to further installation best practice

**100x55mm Ezi-Flow Series aluminium extruded downpipe system contributes to compliance by –**

**E1/AS1 section 4.1.1:** “Materials for downpipes shall comply with the standards stated in Table 4 (AS 1397)”.

- Manufactured from extruded aluminium pipe to AS 1866

**E1/AS1 section 4.1.2:** “Downpipes, gutters, roofing, fastenings and all adjoining components shall be of the same or a compatible material to eliminate the risk of galvanic corrosion.”

- All materials shown in table 1 of this BPIR are compatible with each other.

**E1/AS1 section 4.2.1:** “Downpipes size using Table 5 are acceptable. Other downpipes are acceptable provided their cross-sectional area is no less than that required by Table, and they permit passage of a 50mm diameter sphere.”

- Downpipe size is bigger than 50mm diameter.

**E2/AS1 Table 20:** “Material Selection”

- The product is classified as “Sheltered” and material selection shown in Table 1 of this BPIR meets the requirements of table 20 for exposure Zones B,C, D & E: “Aluminium” materials.

**E2/AS1 Table 21 & Table 22:** “Compatibility of material in contact and subject to run-off.”

- All of the materials shown in table 1 of this BPIR are compatible in contact and run-off with each other provided they are installed and run-off onto compatible materials.

**Continuous Group Limited - Building Product Information – 100x55mm Ezi-Flo downpipe system**

**AS/NZS 2179.1.2014 Section 2.2.2:** “Aluminium alloys for the manufacture of rainwater goods shall be of the 1000, 3000, 5000 or 6000 series complying with AS/NZS 1734, AS/NZS 1866 or AS/NZS 1867”

- Manufactured from 1.9mm BMT extruded Aluminium, Grade 6060 T5 to AS/NZS 1866 - Powder coated

**AS/NZS 2179.1.2014 section 2.2.3:** “Aluminium alloys for the manufacture of accessories shall comply with clause 2.2.2 if not used for castings, or AS 1872 if used for castings”.

- Brackets, bends, tees and joiners are diecast and manufactured to AS 1872.

**AS/NZS 2179.1.2014 Section 3.5 and Table 3.3:** “The minimum base metal thickness (BMT) of vertical or graded downpipes of cross sectional areas less than 75,000mm shall be as specified in Table 3.3 or 3.4 as appropriate.”

- 100x55EF downpipes exceeds the minimum BMT specification required as detailed in table 3.3

**B2/AS1 Table 1:** “Durability Requirements of Nominated Building Element- requires external downpipes to have a durability of 5 Years”.

- 15 year warranty is provided with this downpipe system provided the maintenance conditions are met.

**NZMRM Code of Practice V23.09: This information is included to assist with further information outside of building code compliance.**

**5** The objective of roof drainage systems is to maintain a weatherproof building, to minimise the risk of injury or inconvenience due to flooding, and to avoid potential monetary loss and property damage – including to the contents of buildings.

Roof drainage design requires consideration of: Outlet and downpipe capacity.

**5.3.2A** Rainfall intensity

**5.3.2B** North Island Rainfall Intensity Map

**5.3.2C** South Island Rainfall Intensity Map

**5.7.1** Placement of downpipes significantly affects gutter and downpipe calculations. Diagram 5.7.1A of the Code of Practice is adhered to.

**5.7.2** The use of Table 5.7.2A of the Code of Practice to be utilised in identifying the size of downpipe that is required together with the online calculators noted below.

**5.7.3** Online Downpipe Calculator.

**Supporting documentation**

The following additional documentation supports the above statements:

Document name	Weblinks
Ezi-Flow Series Brochure & Specification Document	<a href="#">Ezi-flow Downpipes Brochure and Specification 2021.pdf</a>
Ezi-Flow Downpipe & Component BPIS Document	<a href="#">Roofing Industries BPIS Document</a>
Maintenance Document	<a href="#">National maintenance document.pdf</a>
Material Compatibility Selection	<a href="#">Continuous Group Material Compatibility Material Selection v1.pdf</a>
Material Compatibility in Contact	<a href="#">Continuous Group Material Compatibility - Compatibility of materials in contact v1.pdf</a>
Material Compatibility subject to Run Off	<a href="#">Continuous Group Material Compatibility - Compatibility of materials subject to run off v1.pdf</a>
Warranty Document	<a href="#">Continuous Group Warranties</a>