

Product and manufacturer details	
Product Name:	180 S-Line pre-painted centre metal fascia soaker
Product Identifier:	18SSCPM-COM
Manufacturer’s Name & Address	Continuous Group Ltd, 6 Yashili Drive, Pokeno 2402
Manufacturer’s Email Address	cg@continuous.co.nz
Manufacturer’s Web Address	www.continuous.co.nz
Manufacturer’s NZBN	9429034817001
Place of Manufacture	Aotearoa New Zealand
Warnings & Bans	No

Product description

180 S-Line pre-painted centre metal fascia soaker is a component used in the installation of the S-Line fascia system.

Table 1

System Components	Component - Material
CG 180 S-Line Centre Soaker	Manufactured from “Factory Painted” pre-painted metal that complies with NZS:2728 (Eg: ColorCote or Colorsteel brands) Minimum 0.50mm BMT, grade G300 steel with minimum 200gsm zinc/alloy coating (Type 6)

Installation Requirements

Refer to BPIR:18SPM-SYS:2023:v1 pre-painted metal fascia system for full system and installation details.

Scope of use

180 S-Line pre-painted centre metal fascia soakers are designed to fit S-Line fascia.

Limitations of the use of this building product:

1. The component cannot be installed onto incompatible materials. The component cannot run-off onto incompatible materials. Material Compatibility, Contact and Run off to be adhered to in accordance with E2/AS1 Table 20, 21 & 22
2. The component cannot be used in Exposure zone “E” (Reference E2/AS1-table 20)
3. Site locations must be evaluated in areas with high wind &/or salt &/or thermal/industrial atmospheric conditions. These types of locations may require specific engineering design (SED). Designers must consult metal supplier’s information for specific durability requirements (Reference E2/AS1 table 20)

Maintenance Requirements

(Link to Care and Maintenance Document below under “Supporting Documentation”)

1. Inspection of the product is required every 3 months to check for buildup of residue and organic matter on the face and underside of the fascia.
2. Wash the painted surface of the product at a minimum of every 6 months and immediately after inspection when required.

Continuous Group Limited - Building Product Information – 180 S-Line pre-painted right hand metal fascia soaker

Relevant building code clauses.

Compliance/Regulation	Detail
NZBC B1 Structure	B1.3.1, B1.3.2, B1.3.3
E2/AS1 External Moisture	Table 20

180 S-Line pre-painted centre metal fascia soaker contributes to compliance by –

NZBC B1 Structure sections 3.1, 3.2 & 3.3

- The materials shown in Table 1 meet performance requirements of B1.3.1, 3.2 and 3.3.

E2/AS1 Table 20: “Material Selection”

- The 180 S-Line Fascia soaker is classified as “Sheltered” and material selection shown in Table 1 of this BPIR meets the requirements of table 20 for exposure Zones B,C & D: “Factory painted” material to NZS 2728 (Type 6)

Supporting documentation

The following additional documentation supports the above statements:

Document name	Weblinks
180mm S-Line Fascia Brochure & Specification Document	180 S-Line Fascia Brochure and Specification 2021.pdf
180mm S-Line Construction & Drop Height Details	180 S-Line Fascia Construction and Drop Height Details Metal and Concrete Roofing 2021.pdf
Colorcote BPIR Document	Colorcote - MagnaFlow Datasheet 2023-1.pdf (colorcote.co.nz)
Colorsteel BPIR Document	NZ Steel Product Information Documents
Maintenance Document	Continuous Group Maintenance Document.pdf
Material Compatibility Selection	Continuous Group Material Compatibility - Material Selection v1.pdf
Material Compatibility in Contact	Continuous Group Material Compatibility - Compatibility of materials in contact v1.pdf
Material Compatibility subject to Run Off	Continuous Group Material Compatibility - Compatibility of materials subject to run off v1.pdf
Warranty Document	Continuous Group Warranties